

ZODZ.E118226
Positioning Devices

Page Bottom

Positioning Devices

See General Information for Positioning Devices

YON YU PLASTICS CO LTD
88 SHENG LI RD
RENDE DISTRICT
TAINAN CITY, 71758 TAIWAN

E118226

Nonmetallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg	Bundle Diam, mm (in.)		Loop Tensile Strength, N (lbf)	Operating Temp, °C (°F)		Min Installation Temp, °C (°F)	Resistant to UV Light	Plenum Rating	ANSI/UL 94 Mtl Flame Rating
		Min	Max		Min	Max				
TSL-80-M	Type 21	2	15	70 (16)	85 (185)	-40(-40)	0(32)	@	N/A	V-2
TSL-100-M	Type 21	2	21	80 (18)	85 (185)	-40(-40)	0 (32)	@	N/A	V-2
TSL-120-M		2	28							
TSL-140-M		2.4	34							
TSL-160-M		2.4	40							
TSL-200-M		2.4	55							
TSL-140-I	Type 21	2	34	180 (40)	85 (185)	-40(-40)	0(32)	@	N/A	V-2
TSL-150-I		2	37							
TSL-180-I		2	47							
TSL-200-I		2	54							
TSL-250-I		2	70							
TSL-300-I		2	82							
TSL-370-I		2.4	106							
TSL-120-S	Type 21	2.4	25	220 (50)	85 (185)	-40(-40)	0(32)	@	N/A	V-2
TSL-160-S		3	40							
TSL-190-S		2	54							
TSL-200-S		2	54							
TSL-250-S		2	68							
TSL-290-S		2	81							
TSL-300-S		2	84							
TSL-370-S		2	106							
TSL-385-S		2	114							
TSL-430-S		2	125							
TSL-500-S		2	151							
TSL-530-S		2	160							
TSL-150-LHD		Type 21	3							
TSL-200-	3		54							

LHD										
TSL-290-LHD		3	82							
TSL-370-LHD		3	106							
TSL-450-LHD		3	130							
TSL-540-LHD		3	160							
TSL-430-HD	Type 21	6	115	800 (180)	85 (185)	-40(-40)	0(32)	@	N/A	V-2
TSL-530-HD		6	150							
TSL-610-HD		6	175							
TSL-710-HD		6	185							
TSL-770-HD		6.5	220							
TSL-800-HD		6.5	235							
TSL-910-HD		6.5	278							
TSL-950-HD		6.5	284							
TSL-1020-HD		6.5	355							
TSL-1200-HD		6.5	374							
TSL-1530-HD		6.5	460							
TSL-240-EHD	Type 21	8.5	64	1150 (258)	85 (185)	-40(-40)	0(32)	@	N/A	V-2
TSL-300-EHD		8.5	81							
TSL-400-EHD		22	114							
TSL-500-EHD		22	150							
TSL-600-EHD		42	181							
TSL-700-EHD		42	216							
TSL-800-EHD		42	248							
TSL-1030-EHD		42	312							
RT-150-S	Type 21	2	36	220 (50)	85 (185)	-40(-40)	0(32)	@	N/A	V-2
RT-200-S	Type 21	2	54	220 (50)	85 (185)	-40(-40)	0(32)	@	N/A	V-2
RT-300-S	Type 21	2	85	220 (50)	85 (185)	-40(-40)	0(32)	@	N/A	V-2
RT-385-S	Type 21	2	114	220 (50)	85 (185)	-40(-40)	0(32)	@	N/A	V-2

Fixing Devices Investigated to ANSI/UL 62275

Cat. No.	Type Dsg	Mechanical Strength, N (lbf)	Operating Temp, °C (°F)		Resistant to UV Light	Plenum Rating	ANSI/UL 94 Mtl Flame Rating
			Min	Max			

SDM-101	Type 21	50 (11)	-40(-40)	85 (185)	@	N/A	V-2
SDM-102	Type 21	159(36)	-40(-40)	85 (185)	@	N/A	V-2
SDM-103	Type 21	258 (58)	-40(-40)	85 (185)	@	N/A	V-2

@ - Nonmetallic cable ties manufactured in Black color only have been evaluated for Outdoor use (Resistance to UV).

Last Updated on 2014-08-29

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".

